

SOLAR'S MOST TRUSTED



inter
solar
award

2022
WINNER

REC ALPHA[®] PURE SERIES

DATASHEET

COMPACT PANEL SIZE

410 W_P
20.6 W/FT^2



ELIGIBLE



LEAD-FREE
ROHS COMPLIANT

EXPERIENCE



PERFORMANCE


REC ALPHA[®] PURE SERIES

DATASHEET



GENERAL DATA

Cell Type	132 half-cut bifacial REC heterojunction cells, with lead-free technology
Glass	0.13 in solar glass with anti-reflective surface treatment in accordance with EN12150
Backsheet	Highly resistant polymer (Black)
Frame	Anodized aluminum (Black)
Junction Box	3-part, 3 bypass diodes, lead-free IP68 rated, in accordance with IEC 62790
Connectors	Stäubli MC4 PV-KBT4/KST4 (12AWG) in accordance with IEC 62852, IP68 only when connected
Cable	12 AWG solar cable, 43.3 in + 47.2 in in accordance with EN50618
Dimensions	71.7 x 40 x 1.2 (in 19.9 ft ²)
Weight	45.2 lb
Origin	Made in Singapore



ELECTRICAL DATA

PRODUCT CODE*: RECxxxAA Pure

	390	395	400	405	410
Power Output - P_{max} (W_p)	390	395	400	405	410
Watt Class Sorting - (W)	0/+5	0/+5	0/+5	0/+5	0/+5
Nominal Power Voltage - V_{MPP} (V)	40.6	41.0	41.4	41.8	42.2
Nominal Power Current - I_{MPP} (A)	9.61	9.64	9.67	9.69	9.72
Open Circuit Voltage - V_{OC} (V)	48.4	48.6	48.8	49.1	49.4
Short Circuit Current - I_{SC} (A)	10.38	10.39	10.40	10.41	10.42
Power Density (W/ft^2)	19.6	19.8	20.1	20.4	20.6
Panel Efficiency (%)	21.1	21.4	21.6	21.9	22.2

Power Output - P_{max} (W_p)	297	301	305	308	312
Nominal Power Voltage - V_{MPP} (V)	38.3	38.6	39.0	39.4	39.8
Nominal Power Current - I_{MPP} (A)	7.77	7.79	7.82	7.83	7.85
Open Circuit Voltage - V_{OC} (V)	45.6	45.8	46.0	46.3	46.6
Short Circuit Current - I_{SC} (A)	8.10	8.39	8.40	8.41	8.42

Values at standard test conditions (STC: air mass AM1.5, irradiance 1000 W/m², temperature 77°F (25°C)), based on a production spread with a tolerance of P_{max} , V_{OC} & I_{SC} ±3% within one watt class. Nominal module operating temperature (NMOT: air mass AM1.5, irradiance 800 W/m², temperature 68°F (20°C), windspeed 3.3 ft/s (1 m/s)). *Where xxx indicates the nominal power class (P_{max}) at STC above.

MAXIMUM RATINGS

Operational Temperature	-40 °F - 185 °F
System Voltage	1000 V
Maximum Test Load (front)	+7000 Pa (1571.5 lb/ft ²)
Maximum Test Load (rear)	-4000 Pa (897 lb/ft ²)
Max Series Fuse Rating	25 A
Max Reverse Current	25 A

* See installation manual for mounting instructions.
Design load = Test load / 1.5 (safety factor)

TEMPERATURE RATINGS*

Nominal Module Operating Temperature	44 °C ± 2 °C
Temperature coefficient of P_{max}	-0.24% /K
Temperature coefficient of V_{OC}	-0.24% /K
Temperature coefficient of I_{SC}	0.04% /K

*The temperature coefficients stated are linear values

DELIVERY INFORMATION

Panels per Pallet	33
Panels per 40 ft GP/high cube container	792 (24 Pallets)
Panels per 53 ft truck	858 (26 Pallets)

CERTIFICATIONS

IEC 61215:2016; IEC61730:2016; UL61730	
IEC 62804	PID
IEC 62782	Dynamic Mechanical Load
ISO 11925-2	Ignitability (EN 13501-1 Class E)
IEC 62716	Ammonia Resistance
IEC 61701	Salt Mist
IEC 61215:2016	Hailstone (35mm)
UL 61730	Fire Type 2
IEC 62321	Lead-free acc. to RoHS EU 863/2015
ISO 14001; ISO9001; IEC45001; IEC62941	



Declare.


WARRANTY

	Standard	REC ProTrust	
Installed by an REC Certified Professional	No	Yes	Yes
System Size	All	<25 kW	25-500 kW
Product Warranty (yrs)	20	25	25
Power Warranty (yrs)	25	25	25
Labor Warranty (yrs)	0	25	10
Power in Year 1	98%	98%	98%
Annual Degradation	0.25%	0.25%	0.25%
Power in Year 25	92%	92%	92%

The REC ProTrust Warranty is only available on panels purchased through an REC Certified Solar Professional installer. Warranty conditions apply. See www.recgroup.com for more details

LOW LIGHT BEHAVIOR

Typical low irradiance performance of module at STC:



REC Solar PTE. LTD.
20 Tuas South Ave. 14
Singapore 637312
post@recgroup.com
www.recgroup.com



Available from:

Founded in 1996, REC Group is an international pioneering solar energy company dedicated to empowering consumers with clean, affordable solar power. As Solar's Most Trusted, REC is committed to high quality, innovation, and a low carbon footprint in the solar materials and solar panels it manufactures. Headquartered in Norway with operational headquarters in Singapore, REC also has regional hubs in North America, Europe, and Asia-Pacific.

Specifications subject to change without notice.

Ref: PM-DS-12-06-Rev-10 2.2024